

Crab Fishing Boat Oil Analysis

Written by Dan

Thursday, 22 September 2011 21:20 - Last Updated Thursday, 22 September 2011 21:26



This Boat is

MOBIL Castrol LABS OIL ANALYSIS REPORT		CONTAMINATION	WEAR	OIL CONDITION
		NORMAL	NORMAL	NORMAL
BOAT CAT - Diesel Engine				
Unit Make : (n/a)	Serial No. : (n/a)	Date Rec'd : Apr 15, 2011		
Unit Model : (n/a)	Unit Ref No. : (n/a)	Sample Date : Apr 9, 2011		
Comp Make : CATERPILLAR	Sub No. : AP-69964	Diagnostician : Kevin Marston		
RECOMMENDATION				
Resample at the next service interval to monitor.				
CONTAMINATION				
There is no indication of any contamination in the component.				
0.2 Soot Count after 320 hours				
WEAR				
All component wear rates are normal.				
Metal count's are way below normal after 320 hours				
OIL CONDITION				
The condition of the oil is acceptable for the time in service.				
All Green lights on oil condition				

Report ID - 00DBER (WCAAS) 01677890 - Pg. 1

© 1994-2007 Petro-Canada Inc. All Rights Reserved. 10027111

Crab Fishing Boat Oil Analysis

Written by Dan

Thursday, 22 September 2011 21:20 - Last Updated Thursday, 22 September 2011 21:26

and this one

MOB Castrol LABORECK		CONTAMINATION	NORMAL																																										
MOBILE OIL ANALYSIS REPORT		WEAR	NORMAL																																										
		OIL CONDITION	NORMAL																																										
BOAT KUBOTA - Diesel Engine																																													
Unit Make : (n/a)	Serial No : (n/a)	Date Rec'd : Apr 15, 2011																																											
Unit Model : (n/a)	Serial No : (n/a)	Sample Date : Apr 9, 2011																																											
Comp Make : KUBOTA	Cont. Ref No : (n/a)	Diagnostician : Kevin Marson																																											
Comp Model : SCTL2HSD	Shab No : AFA49955																																												
RECOMMENDATION																																													
Resample at the next service interval to monitor.																																													
<table border="1"> <thead> <tr> <th>Sample Date</th> <th>Current</th> <th>UOM</th> </tr> </thead> <tbody> <tr> <td>Time on Unit</td> <td>2400</td> <td>hrs</td> </tr> <tr> <td>Time on Oil</td> <td>325</td> <td>hrs</td> </tr> <tr> <td>Time on Ftr</td> <td>0</td> <td>hrs</td> </tr> <tr> <td>Oil Mgmt</td> <td>n/a</td> <td>---</td> </tr> <tr> <td>Ftr Mgmt</td> <td>n/a</td> <td>---</td> </tr> </tbody> </table>				Sample Date	Current	UOM	Time on Unit	2400	hrs	Time on Oil	325	hrs	Time on Ftr	0	hrs	Oil Mgmt	n/a	---	Ftr Mgmt	n/a	---																								
Sample Date	Current	UOM																																											
Time on Unit	2400	hrs																																											
Time on Oil	325	hrs																																											
Time on Ftr	0	hrs																																											
Oil Mgmt	n/a	---																																											
Ftr Mgmt	n/a	---																																											
CONTAMINATION																																													
There is no indication of any contamination in the component.																																													
<table border="1"> <thead> <tr> <th>Sample Date</th> <th>Current</th> <th>Abn</th> </tr> </thead> <tbody> <tr> <td>Silicon</td> <td>37</td> <td>15</td> </tr> <tr> <td>Phosphorus</td> <td>12</td> <td>10</td> </tr> <tr> <td>Sodium</td> <td>11</td> <td>50</td> </tr> <tr> <td>Fuel (%)</td> <td><2.0</td> <td>4</td> </tr> <tr> <td>Oilcol</td> <td>---</td> <td>0.05</td> </tr> <tr> <td>Water (%)</td> <td><0.1</td> <td>0.1</td> </tr> <tr> <td>Soot (%)</td> <td>0</td> <td>1</td> </tr> <tr> <td>Sulfation</td> <td>60</td> <td>100</td> </tr> <tr> <td>Nitration</td> <td>31</td> <td>100</td> </tr> </tbody> </table>				Sample Date	Current	Abn	Silicon	37	15	Phosphorus	12	10	Sodium	11	50	Fuel (%)	<2.0	4	Oilcol	---	0.05	Water (%)	<0.1	0.1	Soot (%)	0	1	Sulfation	60	100	Nitration	31	100												
Sample Date	Current	Abn																																											
Silicon	37	15																																											
Phosphorus	12	10																																											
Sodium	11	50																																											
Fuel (%)	<2.0	4																																											
Oilcol	---	0.05																																											
Water (%)	<0.1	0.1																																											
Soot (%)	0	1																																											
Sulfation	60	100																																											
Nitration	31	100																																											
WEAR																																													
All component wear rates are normal.																																													
<table border="1"> <thead> <tr> <th>Sample Date</th> <th>Current</th> <th>Abn</th> </tr> </thead> <tbody> <tr> <td>Iron</td> <td>103</td> <td>100</td> </tr> <tr> <td>Nickel</td> <td>0.5</td> <td>1</td> </tr> <tr> <td>Chromium</td> <td>0.1</td> <td>20</td> </tr> <tr> <td>Titanium</td> <td>0.0</td> <td>1</td> </tr> <tr> <td>Copper</td> <td>0.3</td> <td>310</td> </tr> <tr> <td>Aluminum</td> <td>1.1</td> <td>20</td> </tr> <tr> <td>Tin</td> <td>0.0</td> <td>15</td> </tr> <tr> <td>Lead</td> <td>0.0</td> <td>40</td> </tr> <tr> <td>Silver</td> <td>0.0</td> <td>1</td> </tr> </tbody> </table>				Sample Date	Current	Abn	Iron	103	100	Nickel	0.5	1	Chromium	0.1	20	Titanium	0.0	1	Copper	0.3	310	Aluminum	1.1	20	Tin	0.0	15	Lead	0.0	40	Silver	0.0	1												
Sample Date	Current	Abn																																											
Iron	103	100																																											
Nickel	0.5	1																																											
Chromium	0.1	20																																											
Titanium	0.0	1																																											
Copper	0.3	310																																											
Aluminum	1.1	20																																											
Tin	0.0	15																																											
Lead	0.0	40																																											
Silver	0.0	1																																											
OIL CONDITION																																													
The condition of the oil is acceptable for the time in service.																																													
<table border="1"> <thead> <tr> <th>Sample Date</th> <th>Current</th> <th>Base</th> </tr> </thead> <tbody> <tr> <td>Bores</td> <td>1.6</td> <td></td> </tr> <tr> <td>Shams</td> <td>0.5</td> <td></td> </tr> <tr> <td>Calcium</td> <td>2.00</td> <td></td> </tr> <tr> <td>Magnesium</td> <td>0.3</td> <td></td> </tr> <tr> <td>Antyfoamum</td> <td>1.1</td> <td></td> </tr> <tr> <td>Sulfur</td> <td>0.1</td> <td></td> </tr> <tr> <td>Phosphorus</td> <td>290</td> <td></td> </tr> <tr> <td>Sulfur</td> <td>1221</td> <td></td> </tr> <tr> <td>Zinc</td> <td>1107</td> <td></td> </tr> <tr> <td>Visc@10°C</td> <td>---</td> <td></td> </tr> <tr> <td>Visc@150°C</td> <td>11.6</td> <td></td> </tr> <tr> <td>VI</td> <td>---</td> <td></td> </tr> <tr> <td>Oxidation</td> <td>85</td> <td></td> </tr> </tbody> </table>				Sample Date	Current	Base	Bores	1.6		Shams	0.5		Calcium	2.00		Magnesium	0.3		Antyfoamum	1.1		Sulfur	0.1		Phosphorus	290		Sulfur	1221		Zinc	1107		Visc@10°C	---		Visc@150°C	11.6		VI	---		Oxidation	85	
Sample Date	Current	Base																																											
Bores	1.6																																												
Shams	0.5																																												
Calcium	2.00																																												
Magnesium	0.3																																												
Antyfoamum	1.1																																												
Sulfur	0.1																																												
Phosphorus	290																																												
Sulfur	1221																																												
Zinc	1107																																												
Visc@10°C	---																																												
Visc@150°C	11.6																																												
VI	---																																												
Oxidation	85																																												

Report ID - GOODER (WCAASIS) 01677899 - Pg. 1

© 1994-2007WacoCheck-Canada Inc. All Rights Reserved. W027111